



# H05VVD3H6-F

## 22G0.75 mm<sup>2</sup>

ESNEK KABLO YAPISI / İNCELTİLMİŞ DIŞ ÇAP / KÜÇÜK BÜKÜLME YARIÇAPI / ALEV GECİKTİRİCİ ÖZELLİK  
FLEXIBLE CABLE DESIGN / REDUCED OUTER DIAMETER / SMALL BENDING RADIUS / FLAME RETARDANT CHARACTERISTIC



CONDUCTIVE	Section	0.75 mm <sup>2</sup>
	Standard	EN 60228 Class-5 Stranded Electrolytic Bare Copper
	Resistance	<25.5 Ohm/km (20°C)
	Construction	24 x 0,20 mm Electrolytic Bare Copper
CORE INSULATION	Material	TS EN 50363-3 T2 PVC
	Standard	TS EN 50363-3
	Elongation	> %170
	Tensile Strength	> 12 N/mm <sup>2</sup>
	Fire Performance Standard	TS EN 60332-1-2
	Marking	White On Black Number +Yellow / Green
	Working Temperature	TS EN 50363-3 T5 ( -15°C/ + 70°C)
	UV Protection	AVAILABLE
COVER INSULATION	Material	TS EN 50363-4-1 TM2 PVC Ral 7035
	Standard	TS EN 50363-4-1 TM2 PVC Ral 7035
	Elongation	> %200
	Tensile Strength	> 12 N/mm <sup>2</sup>
	Fire Performance Standard	TS EN 60332-1-2
	Marking	Laser Print
	Working Temperature	TS EN 50363-4-1 TM2 ( -30°C/ + 70°C)
	Color	RAL 7035 GREY / RAL 9005 BLACK
ROPE	PVC Coated Steel Wire on Both Sides of The Cable	
TEST VOLTAGE	2000 V	
WORKING VOLTAGE	300/500 V	
ROPE	AVAILABLE	
FLEXIBILITY	40 X THICK	
MAX. FREE HANGER DISTANCE	100 M	
MAX. WORKING SPEED	1.60 m/s	
PACKING	500- 1000 M	
PRODUCT STANDARD	TS EN 50214:2010	
QUALTY CERTIFICATE	TS EN ISO 9001:2015 ,TSE, TSE HAR , CE, REACH, ROSH, Pb FREE	