


AKISKABLO



TECNICAL SPESIFICATINS TEKNİK ÖZELLİKLER		PVC	HFFR
Conductor / İletken	Section/ Kesit	(0.22- 16 mm ²)	
	Standard / Standart	EN 60228 Class-5 Stranded Electrolytic Bare Copper / TS EN 60228 Sınıf 5 Bükümlü Elektrolitik Bakır Tel	
	Resistance / Direnç	EN 60228 Class-5	
	Construction / Yapı	Stranded Electrolytic Bare Copper / Bükümlü Elektrolitik Bakır Tel	
Core Insulation / Damar İzolasyonu	Material / Malzeme	TS EN 50363-3 T5 PVC	TS EN 50363-3 T5 PVC
	Standard / Standart	TS EN 50363-3	TS EN 50363-3
	Elongation / Uzama	> %220	> %200
	Tensile Strength /Kopma Mukavemeti	> 12 N/mm ²	> 15 N/mm ²)
	Fire Performance Standard Yangın Performans Standardı	TS EN 60332-1-2	TS EN 50363-0 M1 HFFR
	Marking / İşaretleme	Color / Renk	
General / Genel	Working Temperature / Çalışma Sıcaklığı	TS EN 50363-3 T5 (-15 / + 70 °C)	TS EN 50363-3 T5 (-15 / + 70 °C)
	2011/305/EC CRP/ DOP	TS EN 50575+A1 Eac	TS EN 50575+A1 F
	Packing / Paketleme	100/ 200 /500 / 1000 m	
Product Standard / Ürün Standardı	TS EN 50525-2-31		
Factory Standard / Fabrika Standardı	TS EN ISO 9001:2015 QUALITY MANAGEMENT SYSTEM / KALİTE YÖNETİM SİSTEMİ + ERP		
Quality Certificate / Kalite Belgeleri	TSE HAR ,CE, REACH, ROSH, Pb FREE		

FLEXCAB